























Model		length	width	thickness mm	weight gr.
OE 218		165	11	0,3	2,7
				0,4	3,6
				0,5	4,75
OE 219		165	11	0,3	2,7
				0,4	3,6
				0,5	4,75
OE 2219		165	12	0,8	8,7
OE 3219		165	16	0,8	11,5
				1,0	14,5
OE 190		180	11	0,3	3,0
				0,4	4,0
				0,5	5,0
OE 500		198	11	0,6	5,3
			12	0,8	10,0
GE 210		145	11	0,3	2,9
				0,4	3,85
				0,5	4,8
GE 145/ 146		145	11	0,2	1,9
				0,3	2,9
				0,4	3,9
GE 165/ 166		165	11	0,2	2,2
				0,3	3,3
				0,4	4,4
GE 211		165	11	0,2	2,2
				0,3	3,3
				0,4	4,4
GE 300		165	11	0,2	2,2
				0,3	3,3
				0,4	4,4
GE 212		180	11	0,2	2,4
				0,3	3,6
				0,4	4,8

Model		length	width	thickness mm	weight gr.
OE 125		125	11	0,2 0,4 0,5	1,3 2,6 3,3
OE 135		135	11	0,2 0,3 0,4	1,4 2,2 2,9
OE 135		135	12	0,8	6,5
OE 185		140	11	0,2 0,3 0,6	1,5 2,25 4,5
OE 158		140	7 8	0,2 0,4	0,85 2,0
OE 217		140	12	0,65	5,5
OE 3217		140	16	0,8 1,0	9,0 11,2
OE 196		156	8	0,2 0,4	1,2 2,4
OE 197		156	11	0,2 0,3 0,5	1,75 2,65 4,4
OE 2197		156	12	0,8	8,0